
## **PVC SCHEDULE 80**

**INDUSTRIAL PVC PIPE SYSTEM** 

NATIONAL PIPE & PLASTICS a CRH COMPANY

PVC Schedule 80 IPS pressure pipe is manufactured in accordance with the specifications setforth in ASTM Standard D-1785 and is listed with NSF for use in potable water applications, having met standard 14 & 61 requirements. Dark gray in color, our PVC Schedule 80 is manufactured from a rigid polyvinyl chloride compound with a Cell Classification of 12454 as defined in ASTM Standard D-1784.



## **PIPE DIMENSIONS**

Nominal Size (inches)	Avg. O.D.	Minimum Wall Thickness	Pressure Rating @ 73° F (PSI)	Feet Per Pallet
		Schedule 80	Schedule 80	
1/2	.840	.147	850	8100
3/4	1.050	.154	690	4560
1	1.315	.179	630	3000
1-1/4	1.660	.191	520	3600
1-1/2	1.900	.200	470	3300
2	2.375	.218	400	1980
2-1/2	2.875	.276	420	1980
3	3.500	.300	370	920
4	4.500	.337	320	520
6	6.625	.432	280	440
8	8.625	.500	250	280
10	10.750	.593	230	240
12	12.750	.687	230	60

National Pipe's PVC Schedule 80 is a corrosion resistant pressure-rated pipe available in sizes 1/2-12" for use in applications where conveyed fluid temperatures do not exceed 140° F.

Typical applications include: Chemical processing, Plating operations, and potable water applications. high purity or wastewater treatment, as well as other industrial applications.

\* Standard lengths are 20 feet, other lengths available upon request.

